


R32 Multi-Splitsystemen

Binnenunits

Wandunit Performance

Binnenunit			RAK-15QPE	RAK-18RPE	RAK-25RPE	RAK-35RPE	RAK-42RPE	RAK-50RPE
Vermogen	Koelen (min./nom./max.)	kW	0,90-1,60-2,00	0,90-2,00-2,50	0,90-2,50-3,10	0,90-3,50-4,00	1,70-4,20-5,00	1,90-5,00-5,20
	Verwarmen (min./nom./max.)	kW	0,90-1,80-2,00	0,90-2,50-3,20	0,90-3,40-4,40	0,90-4,20-5,00	1,70-5,40-6,00	2,20-6,00-7,30
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m ³ /h	312-350-400-440	312-350-400-440	333-370-430-510	353-420-485-680	353-410-540-720	353-410-540-750
	Verwarmen	m ³ /h	312-350-420-480	312-350-420-480	333-400-500-570	363-480-570-780	380-500-610-800	380-500-610-820
Geluidsdrukkniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-24-30-34	21-24-33-37	22-24-33-40	25-26-36-43	25-28-39-46	25-28-39-46
	Verwarmen	dB(A)	20-24-32-35	19-22-33-38	20-23-34-41	26-27-36-44	27-31-39-46	27-31-39-46
Geluidsvermogeniveau		dB(A)	47	51	54	57	60	60
Afmetingen (h x b x d)		mm	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230	280 x 780 x 230
Gewicht		kg	8,5	8,5	8,5	8,5	8,5	8,5
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-3/8	1/4-3/8	1/4-1/2	1/4-1/2
Diameter afvoer		mm	16	16	16	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits



- RAK-18RPE
- RAK-25RPE
- RAK-35RPE
- RAK-42RPE
- RAK-50RPE



Accessoires voor room-airconditioners zijn combineerbaar met Multizone-units


R32 Multi-Splitsystemen

Binnenunits

Wandunit Shirokuma

Binnenunit			RAK-18QXE	RAK-25RXE	RAK-35RXE	RAK-50RXE
Vermogen	Koelen (min./nom./ max.)	kW	0,90-1,80-2,20	0,90-2,50-3,10	0,90-3,50-4,00	1,90-5,00-5,20
	Verwarmen (min./nom./ max.)	kW	0,90-2,50-3,10	0,90-3,20-4,20	0,90-4,00-4,80	2,20-5,80-7,00
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m ³ /h	300-330-510-600	300-330-510-600	320-340-520-660	350-400-580-720
	Verwarmen	m ³ /h	290-370-560-680	290-370-560-680	310-380-570-720	350-420-620-800
Geluidsdrukkniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-25-30-36	20-27-35-43	22-29-37-45	25-31-39-47
	Verwarmen	dB(A)	20-26-32-38	20-28-36-43	22-30-37-45	25-31-39-48
Geluidsvermogeniveau		dB(A)	49	58	60	60
Afmetingen (h × b × d)		mm	295 × 900 × 210	295 × 900 × 210	295 × 900 × 210	295 × 900 × 210
Gewicht		kg	11	11	11	11
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-3/8	1/4-1/2
Diameter afvoer		mm	16	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits




RAK-25RXE
RAK-35RXE
RAK-50RXE



Kanaalunit

Binnenunit			RAD18QPE	RAD-25RPE	RAD-35RPE	RAD-50RPE	RAD-60RPE
Vermogen	Koelen (min./nom./max.)	kW	0,90-1,80-2,20	0,90-2,50-3,00	0,90-3,50-4,00	1,20-5,00-5,80	1,20-6,00-6,50
	Verwarmen (min./nom./max.)	kW	0,90-2,50-3,10	0,90-3,50-5,50	0,90-4,80-6,60	1,20-6,00-6,80	1,20-7,00-8,00
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m³/h	330-390-450-510	330-390-450-510	330-390-450-510	350-540-800-1.140	350-540-800-1.140
	Verwarmen	m³/h	330-390-450-510	330-390-450-510	330-390-450-510	350-540-800-1.140	350-540-800-1.140
Geluidsdrukniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	30-33-37-41	30-33-37-41	30-33-37-41	29-32-35-39	29-32-35-39
	Verwarmen	dB(A)	30-34-38-42	30-34-38-42	30-34-38-42	29-32-35-40	29-32-35-40
Geluidsvermogeniveau		dB(A)	57	57	57	53	53
Afmetingen (h x b x d)		mm	235 x 750 x 400	235 x 750 x 400	235 x 750 x 400	270 x 900 x 720	270 x 900 x 720
Gewicht		kg	16	16,0	16,0	35,0	35,0
Diameter leidingen	Vloeistof-gas	Inch	1/4-1/2	1/4-1/2	1/4-1/2	1/4-1/2	1/4-1/2
Diameter afvoer		mm	32	32	32	32	32
Condenswaterpomp			inclusief	inclusief	inclusief	inclusief	inclusief
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits



RAD-25RPE
RAD-35RPE

RAD-50RPE
RAD-60RPE
RAD-70PPD



Accessoires voor room-airconditioners zijn combineerbaar met Multizone-units


R32 Multi-Splitsystemen

Binnenunits

Staande unit Shirokuma

Binnenunit			RAF-25RXE	RAF-35RXE	RAF-50RXE
Vermogen	Koelen (min./nom./max.)	kW	0,90-2,50-3,10	0,90-3,50-4,00	0,90-5,00-5,20
	Verwarmen (min./nom./max.)	kW	0,90-3,40-4,40	0,90-4,50-5,00	0,90-6,00-8,10
Luchtdebiet (zeer laag - laag - medium - hoog)	Koelen	m ³ /h	270-390-510-630	270-390-510-660	300-450-540-700
	Verwarmen	m ³ /h	300-420-540-660	300-420-540-660	330-480-570-730
Geluidsdrukniveau (zeer laag - laag - medium - hoog)	Koelen	dB(A)	20-26-31-38	20-26-31-38	22-29-36-42
	Verwarmen	dB(A)	20-26-31-38	20-26-31-38	22-29-36-43
Geluidsvermogeniveau		dB(A)	52	52	56
Afmetingen (h × b × d)		mm	750 × 590 × 215	750 × 590 × 215	750 × 590 × 215
Gewicht		kg	15,0	15,0	15,0
Diameter leidingen	Vloeistof-gas	Inch	1/4-3/8	1/4-3/8	1/4-1/2
Diameter afvoer		mm	16	16	16
Voedingsspanning			1~230 V, 50 Hz	1~230 V, 50 Hz	1~230 V, 50 Hz

Binnenunits



RAF-25RXE
RAF-35RXE
RAF-50RXE

